

The 640 Series

Wall-Mount Faucets with Integral Stops



The 640 Series



Integral Solutions for food service applications.

Introducing a wall-mounted kitchen sink faucet with hot and cold water supply stops built into the faucet body. The new 640 Series is intended for use in the same applications as our popular 540 Series of 8" wall-mount kitchen faucets. These new faucets offer easy serviceability of cartridges with the integration of accessible stop assemblies.

Standard Tools

Stops close and open with standard flat-head screwdriver for fast service.



Interchangeability

Modular body accepts a wide range of Chicago Faucets components.

Integrated Supply Stops

Body contains supply stops before the cartridge so there's no need to turn off main water to fitting for point of use service.

Hassle-Free Installation

7/8" radius adjustable inlet arms offer a wide range of mounting centers – from 6-1/4" to 9-3/4".

Integral Stops

Point of use service with a standard flat-head screw driver.



Model	Spout	Outlet	Handle
640-GN1AE1-317YAB	3-1/2" rigid/swing GN	Full flow	4" wristblade
640-GN1AE1-369YAB	3-1/2" rigid/swing GN	Full flow	2-3/8" lever
640-GN1AE35-317YAB	3-1/2" rigid/swing GN	1.5 GPM laminar	4" wristblade
640-GN1AE35-369YAB	3-1/2" rigid/swing GN	1.5 GPM laminar	2-3/8" lever
640-L12E1-317YAB	12" rigid/swing	Full flow	4" wristblade
640-L12E1-369YAB	12" rigid/swing	Full flow	2-3/8" lever
640-L12E35-317YAB	12" rigid/swing	1.5 GPM laminar	4" wristblade
640-L12E35-369YAB	12" rigid/swing	1.5 GPM laminar	2-3/8" lever
640-L8E1-317YAB	8" rigid/swing	Full flow	4" wristblade
640-L8E1-369YAB	8" rigid/swing	Full flow	2-3/8" lever
640-LES369YAB	-	_	2-3/8" lever
640-LES369YAB	_	_	2-3/8" lever

Model	Spout	Outlet	Handle
640-L8E35-317YAB	8" rigid/swing	1.5 GPM laminar	4" wristblade
640-L8E35-369YAB	8" rigid/swing	1.5 GPM laminar	2-3/8" lever
640-L9E1-317YAB	9" rigid/swing	Full flow	4" wristblade
640-L9E1-369YAB	9" rigid/swing	Full flow	2-3/8" lever
640-L9E35-317YAB	9" rigid/swing	1.5 GPM laminar	4" wristblade
640-L9E35-369YAB	9" rigid/swing	1.5 GPM laminar	2-3/8" lever
640-S6E1-317YAB	6" swing	Full flow	4" wristblade
640-S6E1-369YAB	6" swing	Full flow	2-3/8" lever
640-S6E35-317YAB	6" swing	1.5 GPM laminar	4" wristblade
640-S6E35-369YAB	6" swing	1.5 GPM laminar	2-3/8" lever
640-LES317YAB	_	_	4" wristblade
640-LES369YAB	_	-	2-3/8" lever

Codes & Standards

Certified to NSF/ANSI 61, Section 9

ASME A112.18.1/CSA B125.1 Certified







Certain models compliant with ADA requirements as specified in the Americans with Disabilities Act.







© 2020 The Chicago Faucet Company. Product specifications subject to change without notice.